



**GAS COMPONENTS**



**ELECTRIC COMPONENTS**



**WATER TECHNOLOGY**



**MECHANICAL COMPONENTS**



**TOOLS**

Spare parts suitable for

**NILMA**

Find the complete and up-to-date range of products in our GEV Webshop



# Manufacturer catalogue

The most important spare parts and accessories arranged clearly for every manufacturer

- ✓ Complete product range and all appliance data always up to date in the GEV Webshop
- ✓ Alphabetical Index at the end of the catalogue

## GEV Webshop

[www.gev-online.co.uk](http://www.gev-online.co.uk)

[www.gev-online.com](http://www.gev-online.com)




- 🔍 Add to Favourites
- 🔍 Sign In with email address and usual password
- 🔍 Easy-order – place several items in your basket at the same time
- 🔍 Quick Item search – no login needed



## switches and momentary switches


### proximity switches

			
1			
<b>GEV No.</b>	348206	<b>Ref. No.</b>	30090048
<b>description</b>	proximity switch 3NO cable length 4980mm M30 171261		

### microswitches

#### roller actuated

#### roller 0°

			
1			
<b>GEV No.</b>	345639	<b>Ref. No.</b>	30090014
<b>description</b>	microswitch with roller plunger 230V 16A 1CO connection solder/screw connection L1 49mm ambient temperature max. 125°C thread L 14mm thread M10 mounting distance 25mm actuating force: 300g type MS15-1		

### magnetic switches


#### 55.5x35.5mm


			
1			
<b>GEV No.</b>	344999	<b>Ref. No.</b>	51410402
<b>description</b>	magnet holder 24V 0.1A P max. 2.5W 1NO connection male faston 6.3mm L 60mm L1 40mm mounting measurements 55.5x35.5mm		

## timers

### mechanical timers


			
1			
<b>GEV No.</b>	350216	<b>Ref. No.</b>	30070036
<b>description</b>	timer 600 2-pole operation time 240s impulse mechanical at 250V 15A permanent position no shaft ø 6x4.6mm shaft 6x4.6mm shaft L 21mm mounting distance 28mm connection lateral		

			
1			
<b>GEV No.</b>	350190	<b>Ref. No.</b>	30070046
<b>description</b>	timer 601 2-pole operation time 4min impulse mechanical 2CO at 250V 16A shaft ø 6x4.6mm shaft L 21mm mounting distance 38.5mm connection male faston 6.3mm DIEHL ambient temperature max. 85°C		

			
1			
<b>GEV No.</b>	350195	<b>Ref. No.</b>	30070038
<b>description</b>	timer M2 2-pole operation time 15min impulse mechanical 2NO at 250V 16A permanent position no shaft ø 6x4.6mm shaft 6x4.6mm shaft L 22mm mounting distance 28mm mounting thread M4 connection male faston 6.3mm		

## alarm devices

### buzzer boards

			
1			
<b>GEV No.</b>	350152	<b>Ref. No.</b>	30150001
<b>description</b>	buzzer board 24V connection male faston 4.8mm		

## relays

### time relays

#### time relays

			
1			
<b>GEV No.</b>	360537	<b>Ref. No.</b>	30000050
<b>description</b>	time relay OMRON H3DK-S1 time range 0.1s-1200h 24-240V AC/DC 5A connection screw clamp		



## electronic controllers

### EVCO - EVERY CONTROL

universal controllers

DIN rail



1

<b>GEV No.</b>	378284	<b>Ref. No.</b>	40163057
<b>description</b>	electronic controller EVERY CONTROL type EC6-133 24V voltage AC Pt100 -50 up to +600°C		

## pumps




### wash and rinse pumps


FIR

pumps



1

<b>GEV No.</b>	500034	<b>Ref. No.</b>	36100007
<b>description</b>	pump inlet $\phi$ 63mm outlet $\phi$ 47mm type 1293.3500 230/400V 50Hz 3 phase 0.55kW 0.75HP L 300mm rotation direction right FIR		
<b>spare parts for</b>	500034		
	<b>GEV No.</b>	510601	<b>Ref. No.</b> 36400037
	impeller $\phi$ 103mm H 25mm rotation direction right thread M8L seat $\phi$ 12.2mm blades 6		
	<b>GEV No.</b>	510693	<b>Ref. No.</b> 36400020
	mechanical shaft seal for shaft $\phi$ 12mm slide ring ext. $\phi$ 24mm slide ring H 15.5mm slide ring int. $\phi$ 11mm counter ring mounting $\phi$ 24mm height counter ring 8mm counter ring int. $\phi$ 13.5mm		
	<b>GEV No.</b>	521513	<b>Ref. No.</b> —
	pump cover FIR inlet $\phi$ 63mm outlet $\phi$ 47mm turn direction right ID $\phi$ 150mm inner height 32mm		

<b>spare parts for</b>	500034		
	<b>GEV No.</b>	524416	<b>Ref. No.</b> 36400028
	pump cover gasket thickness 4x4mm Qty 1 pcs		

## gas valves and ignition boxes

### gas control valves

HONEYWELL



1

<b>GEV No.</b>	107762	<b>Ref. No.</b>	40120186
<b>description</b>	gas valve type VR4605C 230V 50Hz gas inlet flange 32x32mm gas outlet 1/2" thermocouple connection pilot connection pressure range 3-37mbar max 60mbar operator type 220/240V (V404A 1071 4) pressure controller type V5306E 1143 1 HONEYWELL		

### ignition boxes

HONEYWELL



1

<b>GEV No.</b>	106949	<b>Ref. No.</b>	40120188
<b>description</b>	ignition box HONEYWELL type S4960A 1008 electrodes 1 waiting time 2s safety time 10s 220-240V 10VA 50Hz		



# transmission technology and ball bearings

## ball bearings

### deep-groove ball bearings 2RS



1

<b>GEV No.</b>	523509	<b>Ref. No.</b>	40284010
<b>description</b>	deep-groove ball bearing type 6201-2RS shaft $\varnothing$ 12mm ED $\varnothing$ 32mm W 10mm with sealing discs deep-groove ball bearing DIN 625-1		



**A**

alarm devices 3

**E**

electronic controllers 4

**G**

gas control valves 4

**I**

ignition boxes 4

**M**

magnetic switches 3

mechanical timers 3

microswitches 3

**P**

pumps 4

**R**

relays 3

**S**

switches and momentary switches 3

**T**

time relays 3

timers 3

**W**

wash and rinse pumps 4