



**GAS COMPONENTS**



**ELECTRIC COMPONENTS**



**WATER TECHNOLOGY**



**MECHANICAL COMPONENTS**



**TOOLS**

Spare parts suitable for

**THUNDERBIRD**

Find the complete and up-to-date range of products in our GEV Webshop



# Manufacturer catalogue

The most important spare parts and accessories arranged clearly for every manufacturer

- ✓ Complete product range and all appliance data always up to date in the GEV Webshop
- ✓ Alphabetical Index at the end of the catalogue

## GEV Webshop

[www.gev-online.co.uk](http://www.gev-online.co.uk)

[www.gev-online.com](http://www.gev-online.com)



- 🔍 Add to Favourites
- 🔍 Sign In with email address and usual password
- 🔍 Easy-order – place several items in your basket at the same time
- 🔍 Quick Item search – no login needed



## switches and momentary switches

### push/momentary push switches

27.2x22.2mm



1

<b>GEV No.</b>	345092 <sup>1</sup>	<b>Ref. No.</b>	ARM02182
<b>description</b>	momentary push switch mounting measurements 27.2x22.2mm green 2NO 250V 16A illuminated connection male faston 6.3mm ambient temperature max. 85°C protection IP40		

<sup>1</sup>illuminated



1

<b>GEV No.</b>	345090 <sup>1</sup>	<b>Ref. No.</b>	ARM02181
<b>description</b>	momentary push switch mounting measurements 27.2x22.2mm red 2NO 250V 16A illuminated connection male faston 6.3mm ambient temperature max. 85°C protection IP40		

<sup>1</sup>illuminated

### overload switches



1

<b>GEV No.</b>	347815	<b>Ref. No.</b>	ARM0119
<b>description</b>	push switch KJD17 mounting measurements 45x22mm red/green 2NO 250V 10A 0-I connection male faston 6.3mm ambient temperature max. 85°C protection IP54		

### microswitches

#### lever actuated



1

<b>GEV No.</b>	347021	<b>Ref. No.</b>	ARM0125 ARM-02-164
<b>description</b>	microswitch with lever 250V 5A 1CO connection soldering connection L 15mm ambient temperature max. 85°C mounting distance 10mm actuating force: 13g lever length 17mm		

#### roller-lever actuated

#### microswitches



1

<b>GEV No.</b>	346137	<b>Ref. No.</b>	ARM.01.132
<b>description</b>	microswitch with handle with a switch 250V 5A 1CO connection soldering connection L 14mm L1 16.5mm ambient temperature max. 125°C mounting distance 9mm type SS-5GL2 actuating force: 20g black lever length 18mm		

## contactors

### TELEMECANIQUE (Schneider Electric)

#### power contactors



1

<b>GEV No.</b>	380967	<b>Ref. No.</b>	ARM01121 ARM02175
<b>description</b>	power contactor resistive load 20A 230VAC (AC3/400V) 9A/4kW main contacts 3NO auxiliary contacts 1NO connection screw connection type LC1K0910M7		

## equipment-specific units

### for dough mixers

#### agitators



1

<b>GEV No.</b>	692120	<b>Ref. No.</b>	ARM0101
<b>description</b>	beater for dough mixer shaft ø 20 H 230mm W 170mm		



**C**

contactors 3

**M**

microswitches 3

**P**

push/momentary push switches 3

**S**

switches and momentary switches 3