

HVAC CONTROL

RoHS

CE

CE

Series KLT01

Temperature Indicator KLT01

FTPT01-003I_121001



FEATURES:

- Powered directly from the mains.
- One input probe.
- 3 digits (without tenths).
- Probe type NTC or PTC depending on model.
- Red, green or blue display depending on model.
- Error probe indication.
- Connection by screw terminal blocks.

SPECIFICATIONS:

Panel Mounting

Cutout: 71 x 29 mm (2.79 x 1.14 inch)

Dimensions

Front: 76,5 x 36 mm (3.01 x 1.41 inch)

Depth: 62 mm (2.44 inch)

Operating Temperature

-50°C to 150°C / -58°F to 302°F

Accuracy

Better than 1% of full scale

Resolution

1°

Probe

PTC (1000 Ohms, 25°C) or NTC depending on model

IP Protection

Front: IP64

Rear: IP20

HOW TO ORDER:

MODELS: KLT01-PR230C



- C: °C
- F: °F
- 230: 230 Vac
- 110: 115 Vac
- 24: 24 Vac/dc
- 12: 12 Vac/dc
- R: Red display
- G: Green display
- B: Blue display
- P: PTC probe
- N: NTC probe

AVAILABLE MODELS:

- KLT01-NR230C
- KLT01-NR110C

WIRING CONNECTIONS:

Probe



Power supply

KELD



HEADQUARTERS

Polígono Empresarium. C/Lentisco, 15.
50720 La Cartuja Baja. Zaragoza. (Spain)

Tel: +34 976 429 099 · Fax: +34 976 593532

E-mail: keld@keld.es · web: www.keld.es

GPS: N 41.5863 W 0.82531