

HVAC
CONTROL

RoHS **CE**

FTPT08-0011_121009

NTC Temperature Probe



SPECIFICATIONS:

Sensor

NTC

Operating temperature

-50°C to 105°C / -58°F to 221°F

Accuracy

+/- 1% at 25°C

Response time

15 seconds (in air)

Cable

PVC

2 wires 0.35 mm² (22AWG)

Cap

Resinated

6 mm diameter x 25 mm long (0.24 x 0.98 inch)

Stainless Steel

6 mm diameter x 35 mm long (0.24 x 1.38 inch)

Standard length

1.5 meters (4.92 feet)

Other length: Call factory

IP Protection

IP68 (Resinated)

IP67 (Stainless steel)

HOW TO ORDER:

MODEL: PSNTC20



PS: Resinated, 6 mm diameter x 25 mm long

CA: Stainless steel, 6 mm diameter x 35 mm long

AVAILABLE MODELS:

- PSNTC20
- CANTC20

KELD



HEADQUARTERS

Polígono Empresarium. C/Lentisco, 15.
50720 La Cartuja Baja. Zaragoza. (Spain)

Tel: +34 976 429 099 · Fax: +34 976 593532

E-mail: keld@keld.es · web: www.keld.es

GPS: N 41.5863 W 0.82531