



INDICATORI DI UMIDITA' - OMOLOGATI DA UNDERWRITERS LABORATORIES INC.
 MOISTURE INDICATORS - APPROVED BY UNDERWRITERS LABORATORIES INC.
 VOYANT LIQUIDE AVEC INDICATEURS D' HUMIDITE - HOMOLOGUÉS PAR UNDERWRITERS LABORATORIES INC.
 FLÜSSIGKEITSINDIKATOREN - ZUGELASSEN VON UNDERWRITERS LABORATORIES INC.

Disegno Drawing Dessin Zeichnung	N° catalogo Part number N° catalogue Katalog Nr.	Attacchi Connections Raccords Anschlüsse							PS [bar]	TS [°C]		Confezione n° pz Package pcs Emballage Verpackung	
		SAE Flare	ODS		ODM		Per tubo For pipe Pour tuyau Für rohr			min	max		
			Ø [in.]	Ø [mm]	Ø [in.]	Ø [mm]	Ø [in.]	Ø [mm]					Foro Hole Orifice Loch
													Ø [mm]


ATTACCHI SAE FLARE MASCHIO - MASCHIO / SAE FLARE MALE - MALE CONNECTIONS / RACCORDE SAE FLARE MÂLE - MÂLE / BÖRDELANSCHLÜSSE AUSSEN - AUSSEN

	3910/22	1/4"	-	-	-	-	-	-	-	45 (1)	-30	+110	90
	3910/33	3/8"											
	3910/44	1/2"											
	3910/55	5/8"											
	3910/66	3/4"											

ATTACCHI SAE FLARE MASCHIO - FEMMINA / SAE FLARE MALE - FEMALE CONNECTIONS / RACCORDE SAE FLARE MÂLE - FEMELLE / BÖRDELANSCHLÜSSE INNEN - AUSSEN

	3950/22	1/4"	-	-	-	-	-	-	-	45 (1)	-30	+110	90
	3950/33	3/8"											90
	3950/44	1/2"											90
	3950/55	5/8"											90
	3950/66	3/4"											24

ATTACCHI DI RAME A SALDARE / COPPER BRAZE CONNECTIONS / RACCORDE A SOUDER EN CUIVRE / KUPFER LÖTANSCHLÜSSE

	3940/2	-	1/4"	-	-	-	-	-	-	45 (1)	-30	+110	42
	3940/3		3/8"	-									42
	3940/M10		-	10									42
	3940/M12		-	12									42
	3940/4		1/2"	-									42
	3940/5		5/8"	16									42
	3940/M18		-	18									42
	3940/6		3/4"	-									42
	3940/7		7/8"	22									42
	3940/9		1.1/8"	-									17

Note:

- (1): MWP = 435 psi in conformità a omologazione UL
- (1): MWP = 435 psi according to UL approval
- (1): MWP = 435 psi conformément à homologation UL
- (1): MWP = 435 psi in Übereinstimmung zur UL-Zulassung