

Artikelnummer / Article number: LF5039016

DEU

MAGNETVENTIL PARKER 3-WEGE 230V 50Hz
VE141.2YV-Ablauf \varnothing 1/8" kegelf.-Anschlüsse \varnothing 1/4
Dichtung aus VITON - Öffnung \varnothing 3 mm
mit Spule ZB09 9W 220/230V 50/60Hz
Flüssigkeitstemperatur -10°C+140°C

ENU

3-WAY PARKER SOLENOID VALVE 230V 50Hz
VE141.2YV - tapered outlet \varnothing 1/8" - fittings \varnothing 1/4
VITON seal - orifice \varnothing 3 mm
with coil ZB09 9W 220/230V 50/60Hz
fluid temperature -10°C+140°C

ESP

ELETTROVÁLVULA PARKER 3 VÍAS 230V 50Hz
VE141.2YV - desagüe \varnothing 1/8" cónico - conexiones \varnothing 1/4
estanqueidad de VITON - abertura \varnothing 3 mm
con bobina ZB09 9W 220/230V 50/60Hz
temperatura fluidos -10°C+140°C

FRA

ELECTROVANNE PARKER 3 VOIES 230V 50Hz
VE141.2YV - sortie \varnothing 1/8" conique - fixation \varnothing 1/4
joint en VITON - orifice \varnothing 3 mm
avec bobine ZB09 9W 220/230V 50/60Hz
température fluide -10°C+140°C

ITA

ELETTROVALVOLA PARKER 3 VIE 230V 50Hz
VE141.2YV - scarico \varnothing 1/8" conico - attacchi \varnothing 1/4

tenuta in VITON - orificio \varnothing 3 mm

con bobina ZB09 9W 220/230V 50/60Hz

temperatura fluidi $-10^{\circ}\text{C}+140^{\circ}\text{C}$