

## Artikelnummer / Article number: LF5069160

### DEU

MAGNETVENTIL PARKER 3 WEGE 24VAC 50Hz  
VE141GV - Ablauf  $\varnothing$  1/8" Konisch - Anschlüsse  $\varnothing$  1/4  
VITON Befestigung - Öffnung  $\varnothing$  2,5 mm  
mit Spule ZB09 9W 24VAC 50/60Hz  
Flüssigkeitstemperatur -10°C+140°C

### ENU

SOLENOID VALVE PARKER 3 WAYS 24VAC 50Hz  
VE141GV - drain  $\varnothing$  1/8" conical - connections  $\varnothing$  1/4  
VITON seal - orifice  $\varnothing$  2.5 mm  
with coil ZB09 9W 24VAC 50/60Hz  
liquid temperature -10°C+140°C

### ESP

ELECTROVÁLVULA PARKER 3 VIAS 24VAC 50Hz  
VE141GV - desagüe  $\varnothing$  1/8" cónico - conexiones  $\varnothing$  1/4  
cierre de VITON - orificio  $\varnothing$  2,5 mm  
con bobina ZB09 9W 24VAC 50/60Hz  
temperatura fluidos -10°C+140°C

### FRA

ELECTROVANNE PARKER 3 VOIES 24VAC 50Hz  
VE141GV - vidange  $\varnothing$  1/8" conique - fixations  $\varnothing$  1/4  
tenue à VITON - orifice  $\varnothing$  2,5 mm  
avec bobine ZB09 9W 24VAC 50/60Hz  
température des fluides -10°C+140°C

### ITA

ELETTROVALVOLA PARKER 3 VIE 24VAC 50Hz  
VE141GV - scarico  $\varnothing$  1/8" conico - attacchi  $\varnothing$  1/4"

tenuta in VITON - orificio  $\varnothing$  2,5 mm

con bobina ZB09 9W 24VAC 50/60Hz

temperatura fluidi  $-10^{\circ}\text{C}+140^{\circ}\text{C}$