

## Artikelnummer / Article number: LF1120238

### DEU

MAGNETVENTIL CEME 2 WEGE  $\varnothing$  1/8"F 120V

VERNICKELTER KÖRPER

5220 - max 13bar

Dichtung aus Viton - Öffnung  $\varnothing$  2,0 mm

mit Spule B4 14VA 100/120V 60Hz

Flüssigkeitstemperatur -10°C+140°C

### ENU

2-WAY SOLENOID VALVE CEME  $\varnothing$  1/8"F 120V

NICKEL PLATED CASE

5220 - max 13bar

VITON seal - orifice  $\varnothing$  2.0 mm

with coil B4 14VA 100/120V 60Hz

fluid temperature -10°C+140°C

### ESP

ELECTROVÁLVULA CEME 2 VÍAS  $\varnothing$  1/8"F 120V

CUERPO NIQUELADO

5220 - máx 13bar

estanqueidad de VITÓN - abertura  $\varnothing$  2,0 mm

con bobina B4 14VA 100/120V 60Hz

temperatura fluidos -10°C+140°C

### FRA

ELECTROVANNE CEME 2 VOIES  $\varnothing$  1/8"F 120V

corps nickelé

5220 - max. 13 bar

joint en VITON - orifice  $\varnothing$  2,0 mm

avec bobine B4 14VA 100/120V 60Hz

température du fluides -10°C+140°C

ITA

ELETTRORVALVOLA CEME 2 VIE  $\varnothing$  1/8" F 120V

CORPO NICHELATO

5220 - max 13bar

tenuta in VITON - orificio  $\varnothing$  2,0 mm

con bobina B4 14VA 100/120V 60Hz

temperatura fluidi -10°C+140°C