

Artikelnummer / Article number: LF1120233

DEU

MAGNETVENTIL CEME 3 WEGE Ø 1/8" F 230V

KOLLEKTOR AUS INOX

5320 - Abfluss Ø 7 mm - max 14bar

Dichtung aus Viton - Öffnung Ø 1,2 mm

mit Spule B4 13,5VA 230V 50Hz

Flüssigkeitstemperatur -10°C+140°C

ENU

3-WAY SOLENOID VALVE CEME Ø 1/8" F 230V

STAINLESS STEEL SLEEVE

5320 - outlet Ø 7 mm - max 14bar

VITON seal - orifice Ø 1.2 mm

with coil B4 13.5VA 230V 50Hz

fluid temperature -10°C+140°C

ESP

ELECTROVÁLVULA CEME 3 VÍAS Ø 1/8" F 230V

MANGA INOX

5320 - desagüe Ø 7 mm - máx 14bar

estanqueidad de VITÓN - abertura Ø 1,2 mm

con bobina B4 13,5VA 230V 50Hz

temperatura fluidos -10°C+140°C

FRA

ELECTROVANNE CEME 3 VOIES Ø 1/8" F 230V

corps nickelé

5320 - sortie Ø 7 mm - max. 14 bar

joint en VITON - orifice Ø 1,2 mm

avec bobine B4 13,5VA 230V 50Hz

température du fluide -10°C+140°C

ITA

ELETTROVALVOLA CEME 3 VIE Ø 1/8" F 230V

CANOTTO INOX

5320 - scarico Ø 7 mm - max 14bar

tenuta in VITON - orificio Ø 1,2 mm

con bobina B4 13,5VA 230V 50Hz

temperatura fluidi -10°C+140°C