

Artikelnummer / Article number: LF1120349

DEU

3-WEGE MAGNETVENTIL PARKER 230V 50/60Hz

VE128IR - kegelförmiger Abfluss $\varnothing$ 1/8" -max 10 bar

Dichtung aus RUBIN - Loch $\varnothing$ 1,3 mm

mit Spule YB09 9W 220/230V 50/60Hz

Flüssigkeitstemperatur -30°C+140°C

ENU

3-WAY SOLENOID VALVE PARKER 230V 50/60Hz

VE128IR - drain $\varnothing$ 1/8" conical - max 10 bar

RUBY seal - orifice $\varnothing$ 1.3 mm

with coil YB09 9W 220/230V 50/60Hz

fluid temperature -30°C+140°C

ESP

ELECTROVÁLVULA PARKER 3VÍAS 230V 50/60Hz

VE128IR - desagüe $\varnothing$ 1/8" cónico - máx 10 bar

estanqueidad de RUBÍ - abertura $\varnothing$ 1,3 mm

con bobina YB09 9W 220/230V 50/60Hz

temperatura líquidos -30°C +140°C

FRA

ELECTROVANNE PARKER 3 VOIES 230V 50/60Hz

VE128IR - raccord conique $\varnothing$ 1/8" - max. 10 bar

joint en RUBIS - orifice $\varnothing$ 1,3 mm

avec bobine YB09 9W 220/230V 50/60Hz

température fluides -30°C+140°C

ITA

ELETTROVALVOLA PARKER 3 VIE 230V 50/60Hz

VE128IR - scarico $\varnothing$ 1/8" conico - max 10 bar

tenuta in RUBINO - orifizio $\varnothing$ 1,3 mm
con bobina YB09 9W 220/230V 50/60Hz
temperatura fluidi -30°C+140°C