

Artikelnummer / Article number: LF1120701

DEU

MAGNETVENTIL PARKER 2 WEGE 220/240V 9W
2019F1GRG7 - max 20 bar
Dichtung aus RUBIN - Öffnung \varnothing 1,5 mm
mit Spule 483510S6 XS03XS6F 9W 220/240V 50/60Hz
Magnetventilkörper EDELSTAHL - NSF
Flüssigkeitstemperatur -40°C+140°C

ENU

2-WAY SOLENOID VALVE PARKER 220/240V 9W
2019F1GRG7 - max 20 bar
RUBY seal - orifice \varnothing 1.5 mm
with coil 483510S6 XS03XS6F 9W 220/240V 50/60Hz
STAINLESS STEEL solenoid valve housing - NSF
fluids temperature -40°C+140°C

ESP

ELECTROVÁLVULA PARKER 2 VÍAS 220/240V 9W
2019F1GRG7 - máx 20 bar
estanqueidad de RUBÍ - abertura \varnothing 1,5 mm
con bobina 483510S6 XS03XS6F 9W 220/240V 50/60Hz
cuerpo electroválvula INOX - NSF
temperatura fluidos -40°C+140°C

FRA

ELECTROVANNE PARKER 2 VOIES 220/240V 9W
2019F1GRG7 - max. 20 bar
joint en RUBIS - orifice \varnothing 1,5 mm
avec bobine 483510S6 XS03XS6F 9W 220/240V 50/60Hz
corps électrovanne INOX - NSF
température fluides -40°C+140°C

ITA

ELETTROVALVOLA PARKER 2 VIE 220/240V 9W

2019F1GRG7 - max 20 bar

tenuta in RUBINO - orificio \varnothing 1,5 mm

con bobina 483510S6 XS03XS6F 9W 220/240V 50/60Hz

corpo elettrovalvola INOX - NSF

temperatura fluidi -40°C+140°C