

## Artikelnummer / Article number: LF1120751

### DEU

MAGNETVENTIL PARKER 3 WEGE 24VAC 9W  
3019F1GRG7 - Ablauf  $\varnothing$  1/8"F - max 14 bar  
Dichtung aus RUBIN - Öffnung  $\varnothing$  1,5 mm  
mit Spule 483510P0 XS03MF 9W 24VAC 50/60Hz  
Magnetventilkörper EDELSTAHL - NSF  
Flüssigkeitstemperatur -40°C+140°C

### ENU

3-WAY SOLENOID VALVE PARKER 24VAC 9W  
3019F1GRG7 - drain  $\varnothing$  1/8"F - max 14 bar  
RUBY seal - orifice  $\varnothing$  1.5 mm  
with coil 483510P0 XS03MF 9W 24VAC 50/60Hz  
STAINLESS STEEL solenoid valve housing - NSF  
fluids temperature -40°C+140°C

### ESP

ELECTROVÁLVULA PARKER 3 VÍAS 24VAC 9W  
3019F1GRG7 - desagüe  $\varnothing$  1/8"F - máx 14 bar  
estanqueidad de RUBÍ - abertura  $\varnothing$  1,5 mm  
con bobina 483510P0 XS03MF 9W 24VAC 50/60Hz  
cuerpo electroválvula INOX - NSF  
temperatura fluidos -40°C+140°C

### FRA

ELECTROVANNE PARKER 3 VOIES 24VAC 9W  
3019F1GRG7 - sortie  $\varnothing$  1/8"F - max. 14 bar  
joint en RUBIS - orifice  $\varnothing$  1,5 mm  
avec bobine 483510P0 XS03MF 9W 24VAC 50/60Hz  
corps électrovanne INOX - NSF  
température fluides -40°C+140°C

ITA

ELETTROVALVOLA PARKER 3 VIE 24VAC 9W

3019F1GRG7 - scarico  $\varnothing$  1/8" F - max 14 bar

tenuta in RUBINO - orificio  $\varnothing$  1,5 mm

con bobina 483510P0 XS03MF 9W 24VAC 50/60Hz

corpo elettrovalvola INOX - NSF

temperatura fluidi -40°C+140°C