

Artikelnummer / Article number: LF1515004

DEU

VENTIL FÜR ERHITZER ø1/4"M-2,0bar CE/PED

Eichdruck 2,0 bar

Fördermenge Dampfauslass 43,3 kg/h

Silikondichtung

Betriebstemperatur -30/+160°C

CE/PED-zertifiziertes Ventil

ENU

BOILER VALVE ø 1/4"M - 2.0 bar CE/PED

calibration pressure 2.0 bar

steam outlet flow rate 43.3 Kg/h

silicone seal

operating temperature -30/+160°C

CE/TUV certified valve

ESP

VÁLVULA CALDERA ø 1/4"M - 2,0 bar CE/PED

presión de calibración 2,0 bar

capacidad vaciado vapor 43,3 Kg/h

estanqueidad de silicona

temperatura de ejercicio -30/+160°C

válvula certificada CE/PED

FRA

VALVE CHAUDIERE ø 1/4"M 2,0 bar CE/PED

pression de calibrage 2,0 bar

débit d'évacuation vapeur 43,3 Kg/h

joint silicone

température de service -30/+160°C

valve certifiée CE/PED

ITA

VALVOLA CALDAIA Ø 1/4" M - 2,0 bar CE/PED

pressione di taratura 2,0 bar

portata di scarico vapore 43,3 Kg/h

tenuta in silicone

temperatura d'esercizio -30/+160°C

valvola certificata CE/PED