

Artikelnummer / Article number: LF3346091

DEU

FESTROLLE MIT PLATTE

mit VERZINKTEN Stützen

Maße ø 160x38 - Tragfähigkeit 100 Kg

Befestigungsplatte 140x110 mm

Lochabstand 105-80 mm

ENU

CASTOR FIXED PLATE

with STAINLESS STEEL supports

polypropylene nucleus

ring of thermoplastic rubber

dimension ø 160x38 - capacity 100 Kg

fixing plate 140x110 mm

distance between holes 105-80 mm

ESP

RUEDA FIJA CON PLETINA

con soportes INOX - núcleo de polipropileno

aro de goma termoplastica

dimension ø 160x38 mm - capacidad 100 Kg

placa de anclaje 140x110 mm

dist. entre ejes agujeros 105-80 mm

FRA

ROULETTE FIXE A PLATINE

avec supports INOX - noyau en polypropylène

bandage en caoutchouc thermoplastique

dimensions ø 160x38 mm - charge max. 100 Kg

plaque de fixation 140x110 mm

entre-axe 105-80 mm

ITA

RUOTA FISSA A PIASTRA

con supporti INOX - nucleo in polipropilene

anello in gomma termoplastica

dimensione \varnothing 160x38 mm - portata 100 Kg

piastra di fissaggio 140x110 mm

interasse fori 105-80 mm